

4 November 2008

4 November 2008

- 505/MCO P 4030.19 shall be marked, regardless of exemption for mode of transportation, with proper shipping name of item; flash point of all liquids having a flash point of 200 degrees F. or below; and percentage concentration of acids and corrosive liquids. In addition, the quantity of each hazardous or restricted material included in a container shall be annotated adjacent to the shipping name of the item, e.g., Acetic Acid (80% concentration) -- 1 qt.
- e. On shipments of firearms regardless of mode of transportation, selected elements of identification and contractor data markings shall be omitted or obliterated in accordance with the requirements of MIL-STD-129 regarding sensitive items and packing lists shall be placed only inside the containers.
 - f. Special markings for packages and containers when specified on AFMC Form 158 shall be complied with as a part of MIL-STD-129.
 - g. All special coated terneplate containers shall be marked with the legend:

"CAUTION--DO NOT REUSE AS FOOD CONTAINERS."
 - h. Bar code markings in accordance with MIL-STD-129 shall apply to all units, intermediate and exterior containers for all items going into stock regardless of package size or levels of package specified (including commercial packaging). In addition to the NSN/NATO stock number, the exterior shipping container shall include the 13 digit contract number (plus, if appl1.1.03ofr[e, the.03ofr

3. WARRANTED ITEMS: When the contract contains warranty requirements, warranty information shall be applied on containers and items as follows:
 - a. Container markings shall be as specified in MIL-STD-129. The period or conditions of the warranty shall be specifically stated, i.e., landings, flight hours, operating hours, days from shipping date, etc.
 - b. Items shall be marked in accordance with requirements of MIL-STD-130. Markings shall be located in a manner so as to be conspicuous to the person removing the item from service. When no deleterious effect or functional degradation is caused, the markings shall be black letters on yellow FED-STD-