

LM SPACE PACKAGING STANDARD
P-127
Revision 1.1

PACKAGING OF ELECTRONIC CHASSIS

1. SCOPE

This standard provides methods for packaging electronic chassis. This standard only applies to shipments from Lockheed Martin Space (LM Space) facilities. It does not apply to suppliers. Exceptions or additional requirements shall be specified by the purchase order or work instruction.

2. APPLICABLE DOCUMENTS

The following documents, of the latest issue, form a part of this standard to the extent specified herein.

2.1. LMSSC DOCUMENTS

P-40

General Requirements and Commercial Packaging

MPI-441008

PS 1

Structural Plywood, Interior Grade

3.2. UNIT PACKAGING SUMMARY

Table I – Unit Pack Options

Option No	Chassis Weight	Chassis Height	QUP	Fiberboard Container	Cushioning	Maximum Container Wt
1	Less than 45 lbs	Less than 6"	1	Single Wall	4" Grey Polyurethane	65 lbs
2	Less than 45 lbs	6" or more	1	Single Wall	2" Grey Polyurethane	65 lbs
3	45 lbs to 90					

REVISION HISTORY

Release Date	Rev	Change Description	Responsible Engineer
10-09-2015	0.0	Original Release. Task 15-00056.	Bill Manning
02-03-2022	<u>1.0</u>		